



COOLANT S RM 35

RELIABLE FROST AND CORROSION PROTECTION FOR MODERN ENGINES

DESCRIPTION

COOLANT S RM 35 is a high-quality, ready-to-use coolant based on monoethylene glycol in a mixing ratio of 35% coolant concentrate and 65% demineralised water. It offers reliable frost protection down to -22 °C and combines organic and inorganic inhibitors (hybrid technology) for effective long-term protection.

The coolant reliably protects all common metals in the cooling system, including aluminium, against corrosion, cavitation, rust and deposits. At the same time, it is compatible with seals, plastics and hose materials.

COOLANT S RM 35 is ideal for modern combustion engines as well as for combined heat and power plants and gas engines. The ready-to-use mixture can be poured directly into the cooling system – additional dilution is not necessary and is not recommended.

ADVANTAGES

- Reliable frost protection down to -22 °C
- Long-lasting corrosion protection
- Hybrid technology with silicate-based inhibitor system
- Free from nitrite, amine and phosphate
- Compatible with antifreeze agents of the same specification (mixing with non-hybrid products is not recommended)
- Ideally suited for aluminium components

SPECIFICATIONS

- AFNOR NFR 15-601
- ASTM D3306
- ASTM D4985
- BS 6580
- SAE J814

APPROVALS

- ALL MWM TCG
- CATERPILLAR CG

RECOMMENDATIONS

- BMW GS 94000
- DAF 74001
- JENBACHER TA 1000-0201
- LIEBHERR MAN 324 TYPE NF
- MTU MTL 5048
- MWM TR 0199-99-2091
- VOITH TURBO 172.00225010
- VW TL 774C (G11)



TECHNICAL DATA

characteristic	method	unit	value
density at 15°C	DIN 51757	g/cm ³	1,048
frost protection up to	-	°C	-22
product colouring	DIN 10964	-	blue-green

AVAILABLE PRODUCT SIZES

size	order code	EAN code
20 Ltr.	6230020001	4260742618338
60 Ltr.	6230060001	4260742618369
205 Ltr.	6230205001	4260742618390
1.000 Ltr. IBC	6231000001	4260742618451

NOTE

This publication and the information contained herein are considered accurate at the time of printing. No express or implied warranty or representation is made as to the accuracy or completeness of the data and information contained in this publication. The data provided is based on standardised test procedures under laboratory conditions and is for reference purposes only. The user should ensure that they are using the current version of this data sheet. It is the responsibility of the user to evaluate and use the products with due care, to assess their suitability for the intended application and to comply with all applicable laws and regulations. A safety data sheet can be requested for information on health, safety and environmental aspects. It contains details on the storage, safe handling and disposal of the products. Tributech GmbH is not liable for damage or injury resulting from use of the product in a manner that cannot normally be expected, failure to observe recommendations or hazards associated with the nature of the product. Our products must not be used in aircraft or spacecraft or parts thereof. Our General Terms and Conditions of Delivery apply to all deliveries, in particular the liability provisions contained therein. Further product information can be obtained from the application engineering department of Tributech GmbH.

revision date: 01.03.2026