



TAURON X3 5W-40

MODERN ENGINE OIL FOR TOP PERFORMANCE, REDUCED WEAR, AND RELIABLE PROTECTION IN EVERY APPLICATION

DESCRIPTION

TAURON X3 5W-40 is a high-quality premium motor oil designed for modern gasoline, diesel, and gas engines. Thanks to its advanced HC synthetic technology, it guarantees excellent performance and protection under all operating conditions. It ensures optimal cold start performance, low oil consumption, and reduced exhaust emissions, which benefits both the environment and the engine's service life.

The oil is particularly suitable for modern passenger cars, light commercial vehicles, and high-power-density engines, including those with turbochargers and exhaust aftertreatment systems. **TAURON X3 5W-40** offers exceptional protection against wear and corrosion and guarantees reliable lubrication, even under extreme conditions. It supports vehicles with start-stop systems and ensures that engines start faster and more easily.

Thanks to its low content of ash-forming substances (Low SAPS), it helps maintain the functionality of catalytic converters and diesel particulate filters and extends the service life of exhaust aftertreatment systems. It is compatible with a wide range of vehicle brands, including Volkswagen, BMW, Mercedes-Benz, and many Asian and American manufacturers.

ADVANTAGES

- Excellent cold-start performance for quick starts
- Reduced oil consumption thanks to minimized evaporation losses
- Optimized wear protection for longer engine life

- Compatible with exhaust aftertreatment systems (e.g., DPF)
- Wide vehicle compatibility for gasoline, diesel, and gas engines

SPECIFICATIONS

- SAE 5W-40
- EU LEVEL C3
- API SN
- API SP

RECOMMENDATIONS

- BMW LONGLIFE-04
- CHRYSLER MS-10725
- FIAT 9.55535-GH2
- FIAT 9.55535-S2
- FIAT 9.55535-T2
- FORD WSS-M2C917-A
- GM DX2
- GM-LL-A-025
- GM-LL-B-025
- MB 226.5
- MB 229.31
- MB 229.51
- MB 229.52
- OPEL OV0401547
- PORSCHE A40
- PORSCHE C40
- RENAULT RN0700
- RENAULT RN0710
- VW 505 00
- VW 505 01
- VW 511 00



TECHNICAL DATA

characteristic	method	unit	value	size	order code	EAN code
viscosity at 40 °C	DIN 51562-1	mm ² /s	80.0	1 Ltr.	1120001001	4260742613128
viscosity at 100 °C	DIN 51562-1	mm ² /s	14.0	5 Ltr.	1120005001	4260742613210
viscosity index	DIN ISO 2909	-	180	20 Ltr.	1120020001	4260742613418
pour point	DIN ISO 3016	°C	< -35	60 Ltr.	1120060001	4260742614002
flash point	-	°C	225	205 Ltr.	1120205001	4260742614590
density at 15°C	DIN 51757	g/cm ³	0.855	1,000 Ltr. IBC	1121000001	4260742615177
SAE class	SAE J300	-	5W-40	Bulk	1129999901	

AVAILABLE PRODUCT SIZES

NOTE

This publication and the information contained herein are considered accurate at the time of printing. No express or implied warranty or representation is made as to the accuracy or completeness of the data and information contained in this publication. The data provided is based on standardised test procedures under laboratory conditions and is for reference purposes only. The user should ensure that they are using the current version of this data sheet. It is the responsibility of the user to evaluate and use the products with due care, to assess their suitability for the intended application and to comply with all applicable laws and regulations. A safety data sheet can be requested for information on health, safety and environmental aspects. It contains details on the storage, safe handling and disposal of the products. Tributech GmbH is not liable for damage or injury resulting from use of the product in a manner that cannot normally be expected, failure to observe recommendations or hazards associated with the nature of the product. Our products must not be used in aircraft or spacecraft or parts thereof. Our General Terms and Conditions of Delivery apply to all deliveries, in particular the liability provisions contained therein. Further product information can be obtained from the application engineering department of Tributech GmbH.

revision date: 01.06.2026