



TAURON X6 5W-20

INNOVATIVE LOW-VISCOSITY ENGINE OIL FOR EFFICIENT FUEL CONSUMPTION, EXCELLENT ENGINE PROTECTION, AND EXTENDED OIL CHANGE INTERVALS

DESCRIPTION

TAURON X6 5W-20 is a highly advanced low-friction engine oil designed for modern Ford EcoBoost gasoline engines and other vehicles with gasoline engines. It offers outstanding fuel economy while supporting high engine efficiency. Thanks to its advanced additive technology, the oil provides excellent wear protection, even under demanding driving conditions.

The oil delivers excellent cold-start performance and reduces oil consumption, contributing to a longer engine life. Its high thermal-oxidative stability protects the engine from sludge formation and ensures clean and efficient lubrication at all temperatures. In addition, **TAURON X6 5W-20** helps minimize friction losses and reduce engine emissions, which contributes to lower fuel consumption.

For vehicle owners who rely on extended oil change intervals, **TAURON X6 5W-20** offers an ideal solution thanks to its stable properties. It is suitable for all modern Ford vehicles with gasoline engines and is also recommended for engines with and without turbocharging, as well as those with both port and direct injection.

ADVANTAGES

- Significant fuel savings thanks to advanced additive technology
- Excellent wear protection for extended engine life

- Outstanding cold start performance, even at low temperatures
- Reduced oil consumption for efficient lubrication
- High thermal-oxidative stability to prevent sludge formation
- Minimized friction losses for improved engine performance
- Extended oil change intervals

SPECIFICATIONS

- SAE 5W-20
- EU LEVEL C5
- EU LEVEL C6
- API SN
- API SP (RC)
- ILSAC GF-5
- ILSAC GF-6A

RECOMMENDATIONS

- CHRYSLER MS-6395
- FORD WSS-M2C925-A
- FORD WSS-M2C925-B
- FORD WSS-M2C945-A
- FORD WSS-M2C945-B1
- FORD WSS-M2C948-A
- FORD WSS-M2C948-B
- FORD WSS-M2C960-A
- JAGUAR LAND ROVER STJLR.03.5004
- MB 229.71
- MB 229.72



TECHNICAL DATA

characteristic	method	unit	value	size	order code	EAN code
viscosity at 40 °C	DIN 51562-1	mm ² /s	46.0	5 Ltr.	1160005001	4260742613258
viscosity at 100 °C	DIN 51562-1	mm ² /s	8.4	20 Ltr.	1160020001	4260742613456
viscosity index	DIN ISO 2909	-	161	60 Ltr.	1160060001	4260742614040
pour point	DIN ISO 3016	°C	< -35	205 Ltr.	1160205001	4260742614637
flash point	-	°C	205	1,000 Ltr. IBC	1161000001	4260742615214
density at 15°C	DIN 51757	g/cm ³	0.851	Bulk	1169999901	
SAE class	SAE J300	-	5W-20			

AVAILABLE PRODUCT SIZES

NOTE

This publication and the information contained herein are considered accurate at the time of printing. No express or implied warranty or representation is made as to the accuracy or completeness of the data and information contained in this publication. The data provided is based on standardised test procedures under laboratory conditions and is for reference purposes only. The user should ensure that they are using the current version of this data sheet. It is the responsibility of the user to evaluate and use the products with due care, to assess their suitability for the intended application and to comply with all applicable laws and regulations. A safety data sheet can be requested for information on health, safety and environmental aspects. It contains details on the storage, safe handling and disposal of the products. Tributech GmbH is not liable for damage or injury resulting from use of the product in a manner that cannot normally be expected, failure to observe recommendations or hazards associated with the nature of the product. Our products must not be used in aircraft or spacecraft or parts thereof. Our General Terms and Conditions of Delivery apply to all deliveries, in particular the liability provisions contained therein. Further product information can be obtained from the application engineering department of Tributech GmbH.

revision date: 01.06.2026