



XPL 20W-50

SUPER HIGH PERFORMANCE DIESEL (SHPD) ENGINE OIL FOR YEAR-ROUND USE

DESCRIPTION

XPL 20W-50 is a high-performance motor oil specially designed for use in gasoline and diesel engines. Thanks to an advanced blend of selected base oils and modern additives, it offers outstanding performance and protection for engines from a wide range of manufacturers. It is suitable for passenger cars as well as commercial vehicles, work machines, and agricultural machinery. Ideal for engines with or without turbocharging, **XPL 20W-50** ensures maximum efficiency and protects the engine even under extreme operating conditions.

XPL 20W-50 can be used in a wide range of vehicles and machinery. It meets the requirements of many European, American, and Japanese manufacturers and is also suitable for older diesel and gasoline engines in commercial vehicles, buses, and construction machinery. It is recommended to perform a complete oil change to take full advantage of the product and avoid mixing with other engine oils.

SPECIFICATIONS

- SAE J300: 20W-50
- API SL
- API CI-4

RECOMMENDATIONS

- ALLISON C-3
- CAT TO-2
- CCMC D2
- CCMC G2
- DTFR 15B110 (MB 228.3)
- MAN M 3275
- MB 229.1
- MIL-L-2104C
- MIL-L-2104D
- MIL-L-2104E
- MIL-L-46152C
- VOLVO VDS-3

ADVANTAGES

- Provides excellent protection against deposits
- Reliably reduces deposits such as sticking, varnishing, and coking
- Low oil consumption thanks to optimized formula
- Provides outstanding wear protection and high oxidation resistance
- Particularly stable lubricating film even at extreme temperatures
- High shear stability ("stay-in-grade") – ideal for year-round use

TECHNICAL DATA

characteristic	method	unit	value
viscosity at 40 °C	DIN 51562-1	mm ² /s	167.1
viscosity at 100 °C	DIN 51562-1	mm ² /s	20.2
viscosity index	DIN ISO 2909	-	141
pour point	DIN ISO 3016	°C	-36
flash point	-	°C	> 225
density at 15°C	DIN 51757	g/cm ³	0.881
TBN (Total Base Number)	DIN 51639-1	mgKOH/g	10.4
SAE class	SAE J300	-	20W-50



AVAILABLE PRODUCT SIZES

size	order code	EAN code
20 Ltr.	1650020001	4260587426518
200 Ltr.	1650200001	4260587424057

NOTE

This publication and the information contained herein are considered accurate at the time of printing. No express or implied warranty or representation is made as to the accuracy or completeness of the data and information contained in this publication. The data provided is based on standardised test procedures under laboratory conditions and is for reference purposes only. The user should ensure that they are using the current version of this data sheet. It is the responsibility of the user to evaluate and use the products with due care, to assess their suitability for the intended application and to comply with all applicable laws and regulations. A safety data sheet can be requested for information on health, safety and environmental aspects. It contains details on the storage, safe handling and disposal of the products. Tributech GmbH is not liable for damage or injury resulting from use of the product in a manner that cannot normally be expected, failure to observe recommendations or hazards associated with the nature of the product. Our products must not be used in aircraft or spacecraft or parts thereof. Our General Terms and Conditions of Delivery apply to all deliveries, in particular the liability provisions contained therein. Further product information can be obtained from the application engineering department of Tributech GmbH.

revision date: 01.03.2026